

In the Claims

1. (Original) An apparatus, comprising:
a fuel cell for producing a flow of electric charges from a fuel;
an electric charge counter coupled with the fuel cell, wherein counted electric charges are proportional to an amount of the fuel used in the fuel cell to produce the counted electric charges; and
a display coupled with the electric charge counter to show an amount of the fuel based on corresponding counted electric charges.
2. (Original) The apparatus as recited in claim 1, wherein the display shows an amount of fuel used by the fuel cell based on the counted electric charges.
3. (Original) The apparatus as recited in claim 1, further comprising a fuel supply, wherein the display shows an amount of fuel remaining in the fuel supply after subtracting the amount of fuel corresponding to the counted electric charges.
4. (Original) The apparatus as recited in claim 1, wherein the electric charge counter counts electric charges by integrating the flow of electric charges with respect to time.

1 5. (Original) The apparatus as recited in claim 4, wherein the electric
2 charge counter counts electric charges by measuring a voltage proportional to a
3 flow rate of the electric charges and assigns a frequency to the voltage.

4
5 6. (Original) The apparatus as recited in claim 5, wherein the electric
6 charge counter varies the frequency in proportion to changes in the flow rate of the
7 electric charges over time.

8
9 7. (Original) The apparatus as recited in claim 6, wherein the electric
10 charge counter increments the count of the electric charges at an incrementing rate
11 proportional to the frequency.

12
13 8. (Original) The apparatus as recited in claim 1, wherein the electric
14 charge counter includes an interpreter to determine a proportionality factor
15 between the counted electric charges and the amount of fuel used to produce the
16 counted electric charges.

17
18 9. (Original) The apparatus as recited in claim 8, further comprising a
19 temperature compensator, wherein the amount of fuel shown on the display is
20 corrected for a temperature if the temperature affects the proportionality between
21 the quantity of counted electric charges and the amount of fuel used to produce the
22 counted electric charges.

10. (Original) The apparatus as recited in claim 8, further comprising a pressure compensator, wherein the amount of fuel shown on the display is corrected for a pressure if the pressure affects the proportionality between the quantity of counted electric charges and the amount of fuel used to produce the counted electric charges.

11. (Original) The apparatus as recited in claim 8, further comprising a fuel loss compensator, wherein the amount of fuel shown on the display is corrected if a fuel loss affects the proportionality between the quantity of counted electric charges and the amount of fuel used to produce the counted electric charges.

12. (Original) The apparatus as recited in claim 8, further comprising a fuel mix compensator, wherein the amount of fuel shown on the display is corrected if a fuel mix affects the proportionality between the quantity of counted electric charges and the amount of fuel used to produce the counted electric charges.

13. (Original) The apparatus as recited in claim 8, further comprising a self-calibrator to determine, while counting electric charges during fuel use, the proportionality between the counted electric charges and the amount of fuel used to produce the counted electric charges.

1 14. (Original) The apparatus as recited in claim 13, wherein the self-
2 calibrator performs automatic determination of the proportionality.

3
4 15. (Original) The apparatus as recited in claim 8, further comprising a
5 fuel comparator to determine electric charge counts for equivalent amounts of
6 different types of fuel.

7
8 16. (Original) A fuel cell, comprising:
9 a means for converting a fuel into a flow of electric charges, wherein the
10 quantity of electric charges produced over time is proportional to the quantity of
11 fuel molecules converted;
12 a means for counting the electric charges in the flow; and
13 a means for displaying an amount of fuel molecules converted.

14
15 17. (Original) The fuel cell as recited in claim 16, wherein the means for
16 displaying shows the amount of fuel molecules converted as an amount of fuel
17 from a fuel supply.

18
19 18. (Original) The fuel cell as recited in claim 17, wherein the means for
20 displaying shows the amount of molecules converted as an amount of fuel
21 remaining in a fuel supply.

19. (Original) The fuel cell as recited in claim 16, wherein the means for counting the electric charges integrates the flow of electric charges with respect to time.

20. (Original) The fuel cell as recited in claim 19, wherein the means for counting the electric charges measures a voltage proportional to a flow rate of the electric charges and assigns a frequency to the voltage.

21. (Original) The fuel cell as recited in claim 20, wherein the electric charge counter varies the frequency in proportion to changes in the flow rate of electric charges over time.

22. (Original) The fuel cell as recited in claim 21, wherein the electric charge counter increments the count of the electric charges at an incrementing rate proportional to the frequency.

23. (Original) The fuel cell as recited in claim 16, wherein the means for counting electric charges measures an overall power output of the fuel cell over time when connected to a particular electrical load and correlates the overall power output of the fuel cell over time to the quantity of fuel molecules converted using an efficiency factor of the fuel cell when connected to the particular electrical load.

1 24. (Original) The fuel cell as recited in claim 16, wherein the means for
2 counting electric charges includes a means for determining a proportionality
3 between the count of the electric charges and the quantity of fuel molecules
4 converted.

5
6 25. (Original) The fuel cell as recited in claim 24, wherein the means for
7 determining a proportionality further comprises a temperature compensator.

8
9 26. (Original) The fuel cell as recited in claim 24, wherein the means for
10 determining a proportionality further comprises a pressure compensator.

11
12 27. (Original) The fuel cell as recited in claim 24, wherein the means for
13 determining a proportionality further comprises a fuel loss compensator.

14
15 28. (Original) The fuel cell as recited in claim 24, wherein the means for
16 determining a proportionality further comprises a fuel mix compensator.

17
18 29. (Original) The fuel cell as recited in claim 24, wherein the means for
19 determining a proportionality further comprises a self-calibrator to determine the
20 proportionality while counting electric charges during fuel use.

21
22 30. (Original) The fuel cell as recited in claim 29, wherein the self-
23 calibrator performs automatic determination of the proportionality.
24
25

1 31. (Original) The fuel cell as recited in claim 16, further including a
2 fuel comparator to determine electric charge counts from equivalent amounts of
3 different types of fuel.
4

5 32. (Original) A fuel supply system, comprising:
6 a fuel container for holding a remaining amount of fuel;
7 an electric charge counter to count an electric charge content of an amount
8 of fuel taken from the fuel container, wherein the count of the electric charge
9 content is proportional to the amount of the fuel taken from the fuel container; and
10 a display to show the remaining amount of fuel in the fuel container.
11

12 33. (Original) The fuel supply system as recited in claim 32, wherein the
13 electric charge content is counted during oxidation of the fuel by a fuel cell.
14

15 34. (Original) The fuel supply system as recited in claim 32, wherein the
16 fuel comprises fuel molecules, and each fuel molecule contributes a constant
17 number of electric charges to the count of the electric charge content.
18

19 35. (Original) A fuel gauge, comprising:
20 a charge counter to count electrical charges produced in a fuel cell by a fuel
21 from a fuel supply; and
22 a display to show an amount of the fuel based on the counted electrical
23 charges.
24
25

1 36. (Original) The fuel gauge as recited in claim 35, wherein the amount
2 of the fuel displayed is an amount of the fuel that has been used from the fuel
3 supply.

4
5 37. (Original) The fuel gauge as recited in claim 35, wherein the amount
6 of the fuel displayed is an amount of the fuel remaining in the fuel supply.

7
8 38. (Withdrawn) A count interpreter for a charge counting fuel gauge,
9 comprising:

10 a count calibrator; and

11 a fuel loss compensator.

12
13 39. (Withdrawn) The count interpreter as recited in claim 38, wherein
14 the count calibrator further includes a temperature compensator to adjust a display
15 of a fuel amount if a charge count is affected by a temperature.

16
17 40. (Withdrawn) The count interpreter as recited in claim 38, wherein
18 the count calibrator further includes a pressure compensator to adjust a display of
19 a fuel amount if a charge count is affected by a pressure.

20
21 41. (Withdrawn) The count interpreter as recited in claim 38, wherein
22 the count calibrator further includes a fuel mix compensator to adjust a display of
23 a fuel amount if a charge count is affected by a fuel mix.

1 42. (Withdrawn) The count interpreter as recited in claim 38, wherein
2 the fuel loss compensator adjusts a fuel amount to be displayed by an amount of
3 fuel that does not contribute to a charge count.
4

5 43. (Withdrawn) The count interpreter as recited in claim 38, further
6 comprising a self-calibrator to find a relationship between an amount of fuel and a
7 quantity of electric charges counted during use of a fuel that produces electric
8 charges in a fuel cell.
9

10 44. (Withdrawn) The count interpreter as recited in claim 38, further
11 comprising a fuel comparator to determine a quantity of electric charges yielded
12 by same amounts of different fuels.
13

14 45. (Original) A method, comprising:
15 producing electric charges in a fuel cell using a fuel;
16 counting the electric charges to determine an amount of the fuel used to
17 produce the electric charges; and
18 displaying the amount.
19

20 46. (Original) The method as recited in claim 45, wherein the producing
21 electric charges using a fuel includes producing a number of electric charges for
22 each molecule of fuel, wherein the number is a constant.
23
24
25

1 47. (Original) The method as recited in claim 45, wherein the electric
2 charges are obtained from an oxidation reaction of the fuel.

3
4 48. (Original) A method, comprising:
5 connecting an electric charge counter to a fuel cell, wherein the fuel cell
6 produces electric charges from a fuel;
7 counting the electric charges; and
8 displaying an amount of fuel corresponding to the counted electric charges.

9
10 49. (Original) The method as recited in claim 48, further comprising
11 displaying an amount of fuel remaining in a fuel supply after an amount of fuel
12 corresponding to the counted electric charges has been subtracted from the fuel
13 supply.

14
15 50. (Original) The method as recited in claim 48, further comprising
16 determining a proportionality factor between a quantity of the counted electric
17 charges and an amount of fuel used by the fuel cell.